

13-FL03

Film Tape

Product Description

A high coat weight double sided PVC tape with incredibly aggressive adhesive making it one of the highest performing double sided film tapes available. Its adhesive system is designed to bond well to medium surface energy substrates.

Product Features

Exceptionally high tack and peel adhesion
Good conformability
Bonds to rough and uneven surfaces
Excellent humidity, solvent & UV resistance
Suitable for outdoor use

Carrier	PVC
Density	N/A
Adhesive Type	Modified Acrylic
Total Thickness	0.310mm
Adhesive Tape Colour	White
Release Liner	Amber Glassine Paper 80gsm
Peel Adhesion (N/25mm)	Very High
Shear Strength	High
Elongation	60 %
Continuous Temp. Range	-30°C to +70°C
Minimum Application Temp.	+ 15°C
Available Widths	3mm – 1240mm
Available Formats	Logs, Rolls, Discs, Pads, Die-cut Shapes
Shelf Life	1 Year stored at 21°C, 50% RH and out of direct sunlight
Common uses (not limited too)	Used across variety of industries & critical bonding applications such as Automotive mirror mounting, kick plates, machine labels, decorative trim, battery pack mounting and plastic mouldings.

Tecman Speciality Materials **A:** Berrington House, Berrington Road, Leamington Spa, Warks. CV31 1NB
T: + 44 (0) 1926 337466 **E:** customerservice@tecmanuk.com **W:** www.tecmanuk.com

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request.